



OLD LINE TANK

- 3) EXTEND ALL CPLGS. 5/8" INSIDE.
- 2) HYDRO @ 163 PSIG. MIN.

NOTE: 1) SEAL ALL OPENINGS TO KEEP CEMENT MOIST TO PREVENT CRACKING.

HEADS	.280" SA-455 2:1 S.E.	CS-72-1950-H	REV. 7-23-04
	(.248" MIN.)		DATE: 4-14-03
SHELL	.250" SA-455	FOR: HANSON TANK	
		HORIZ. WATER TANK.	
M.A.W.P. 125 PSIG. @ 210 °F		215.0 SQ. FT. SURFACE AREA. THIS TANK IS SHIPPED WITH ALL OPENINGS SEALED. THE CEMENT LINING MUST BE KEPT MOIST BEFORE, DURING, AND AFTER INSTALLATION TO PREVENT CRACKING OF THE CEMENT.	
M.D.M.T. -20 °F @ 125 PSIG.		INSIDE: CEMENT LINED (1874)	
ASME. SECTION VIII DIV. 1, 2001 ADD 2003		OUTSIDE: PRIME	
X-RAY: RT-4 SPOT L.S. NOT G.S.		CAD "B" SIZE UNDER "STD"-SERIES	
GALLONS: 1950 WT. 4363 LBS.		BY: J.G. SCALE: 1/2"=12"	
SERIAL NO.		ROY E. HANSON JR. MFG.	
N.B.		1924 COMPTON AVE. LOS ANGELES, CA 90011	